

Monolithic Linear IC

**SANYO**

No.1700E

**L780S00 Series**5 to 24V 1A 5-Pin Voltage Regulators  
with Strobe Pin**Features**

- Output voltage
 




L780S05: 5V	L780S06: 6V	L780S07: 7V
L780S08: 8V	L780S09: 9V	L780S10: 10V
L780S12: 12V	L780S15: 15V	L780S18: 18V
L780S20: 20V	L780S24: 24V	
- The strobe pin can be used to turn ON/OFF output voltage (active-low).
- 1A output current.
- On-chip thermal protector.
- On-chip overcurrent limiter.
- On-chip ASO protector.
- The use of package TO220-5H (5 pins) facilitates mounting and thermal design.

**[Common to L780S00 series]****Maximum Ratings at Ta=25°C**

			unit
Maximum Supply Voltage	$V_{CCmax}$	Pin 1	35 V
Strobe Input Voltage	$V_{STmax}$	Pin 4	18 V
Strobe Input Current	$I_{STmax}$	Pin 4	5 mA
Allowable Power Dissipation	$P_{dmax}$		1.75 W
		$T_c=25^\circ\text{C}$	20 W
Thermal Resistance	$\theta_{j-c}$		5 $^\circ\text{C/W}$
Operating Temperature	$T_{opr}$		-20 to +80 $^\circ\text{C}$
Storage Temperature	$T_{stg}$		-55 to +150 $^\circ\text{C}$

**Strobe Operating Characteristics at Ta=25°C**

	unit
Strobe Operation Start Voltage $V_{st(on)}$	2.4 V
Strobe Operation Stop Voltage $V_{st(off)}$	0.5 V

**DC Characteristics Test Circuit (Common to L780S00 series)****Package Dimensions  
(unit: mm)  
3079**

**SANYO Electric Co., Ltd. Semiconductor Business Headquarters**  
TOKYO OFFICE Tokyo Bldg., 1-10, 1 Chome, Ueno, Taito-ku, TOKYO, 110 JAPAN

8119YT/ N307TA/9047KI/7086KI/4045MW, TS No. 1700-1/9

# L780S00 Series

## L780S05

### Recommended Operating Conditions at $T_a=25^{\circ}\text{C}$

Input Voltage Range	$V_{IN}$	7.5 to 20.0	V
Output Current Range	$I_o$	5 to 1000	mA

### Operating Characteristics at $T_j=25^{\circ}\text{C}, V_{IN}=10\text{V}, I_o=500\text{mA}, V_{st}=0\text{V}, *T_a=25^{\circ}\text{C}$

		min	typ	max	unit
Output Voltage 1	$V_{o1}$	4.8	5.0	5.2	V
Line Regulation 1	$\Delta V_{o1n1}$	$7\text{V} \leq V_{IN} \leq 25\text{V}$	3	100	mV
Line Regulation 2	$\Delta V_{o1n2}$	$8\text{V} \leq V_{IN} \leq 12\text{V}$	1	50	mV
Load Regulation 1	$\Delta V_{o1d1}$	$5\text{mA} \leq I_o \leq 1.5\text{A}$		100	mV
Load Regulation 2	$\Delta V_{o1d2}$	$250\text{mA} \leq I_o \leq 750\text{mA}$		50	mV
Output Voltage 2	$V_{o2}$	$7\text{V} \leq V_{IN} \leq 20\text{V},$ $5\text{mA} \leq V_{IN} \leq 1\text{A}$	4.75	5.25	V
Current Dissipation	$I_{cc}$			8.0	mA
Current Dissipation Variation (Line)	$\Delta I_{cc1n}$	$7\text{V} \leq V_{IN} \leq 25\text{V}$		1.3	mA
Current Dissipation Variation (Load)	$\Delta I_{cc1d}$	$5\text{mA} \leq I_o \leq 1\text{A}$		0.5	mA
Output Noise Voltage	$V_{NO}$	$10\text{Hz} \leq f \leq 100\text{kHz}^*$	40		$\mu\text{V}$
Ripple Rejection	$R_r$	$f=120\text{Hz},$ $8\text{V} \leq V_{IN} \leq 18\text{V}$	62	78	dB
Dropout Voltage	$V_{drop}$	$I_o=1\text{A}$	2.0		V
Output Short Current	$I_{os}$	$V_{IN}=35\text{V}$	0.75		A
Peak Output Current	$I_{op}$		2.2		A
Output Voltage at Strobe Mode	$V_{o(ston)}$	$V_{IN}=35\text{V}, V_{st}=5\text{V},$ $I_o=0, *$		0.8	V
Current Dissipation at Strobe Mode	$I_{cc(ston)}$	"		3.0	mA
Strobe Input Current	$I_{st}$	"		1.0	mA

## L780S06

### Recommended Operating Conditions at $T_a=25^{\circ}\text{C}$

Input Voltage Range	$V_{IN}$	8.5 to 21.0	V
Output Current Range	$I_o$	5 to 1000	mA

### Operating Characteristics at $T_j=25^{\circ}\text{C}, V_{IN}=11\text{V}, I_o=500\text{mA}, V_{st}=0\text{V}, *T_a=25^{\circ}\text{C}$

		min	typ	max	unit
Output Voltage 1	$V_{o1}$	5.75	6.0	6.25	V
Line Regulation 1	$\Delta V_{o1n1}$	$8\text{V} \leq V_{IN} \leq 25\text{V}$	5	120	mV
Line Regulation 2	$\Delta V_{o1n2}$	$9\text{V} \leq V_{IN} \leq 13\text{V}$	1.5	60	mV
Load Regulation 1	$\Delta V_{o1d1}$	$5\text{mA} \leq I_o \leq 1.5\text{A}$		120	mV
Load Regulation 2	$\Delta V_{o1d2}$	$250\text{mA} \leq I_o \leq 750\text{mA}$		60	mV
Output Voltage 2	$V_{o2}$	$8\text{V} \leq V_{IN} \leq 21\text{V},$ $5\text{mA} \leq V_{IN} \leq 1\text{A}$	5.7	6.3	V
Current Dissipation	$I_{cc}$			8.0	mA
Current Dissipation Variation (Line)	$\Delta I_{cc1n}$	$8\text{V} \leq V_{IN} \leq 25\text{V}$		1.3	mA
Current Dissipation Variation (Load)	$\Delta I_{cc1d}$	$5\text{mA} \leq I_o \leq 1\text{A}$		0.5	mA
Output Noise Voltage	$V_{NO}$	$10\text{Hz} \leq f \leq 100\text{kHz}^*$	45		$\mu\text{V}$
Ripple Rejection	$R_r$	$f=120\text{Hz},$ $9\text{V} \leq V_{IN} \leq 19\text{V}$	59	75	dB
Dropout Voltage	$V_{drop}$	$I_o=1\text{A}$	2.0		V
Output Short Current	$I_{os}$	$V_{IN}=35\text{V}$	0.75		A
Peak Output Current	$I_{op}$		2.2		A
Output Voltage at Strobe Mode	$V_{o(ston)}$	$V_{IN}=35\text{V}, V_{st}=5\text{V},$ $I_o=0, *$		0.8	V
Current Dissipation at Strobe Mode	$I_{cc(ston)}$	"		3.0	mA
Strobe Input Current	$I_{st}$	"		1.0	mA

# L780S00 Series

## L780S07

### Recommended Operating Conditions at Ta=25°C

Input Voltage Range	$V_{IN}$	9.5 to 22.0	V
Output Current Range	$I_o$	5 to 1000	mA

### Operating Characteristics at Tj=25°C, $V_{IN}=12V$ , $I_o=500mA$ , $V_{st}=0V$ , \*Ta=25°C

		min	typ	max	unit
Output Voltage 1	$V_{o1}$	6.72	7.0	7.28	V
Line Regulation 1	$\Delta V_{o1n1}$	$9V \leq V_{IN} \leq 26V$	6	140	mV
Line Regulation 2	$\Delta V_{o1n2}$	$10V \leq V_{IN} \leq 14V$	2	70	mV
Load Regulation 1	$\Delta V_{o1d1}$	$5mA \leq I_o \leq 1.5A$		140	mV
Load Regulation 2	$\Delta V_{o1d2}$	$250mA \leq I_o \leq 750mA$		70	mV
Output Voltage 2	$V_{o2}$	$9V \leq V_{IN} \leq 22V$ , $5mA \leq I_{IN} \leq 1A$	6.65	7.35	V
Current Dissipation	$I_{cc}$			8.0	mA
Current Dissipation Variation (Line)	$\Delta I_{cc1n}$	$9V \leq V_{IN} \leq 25V$		1.3	mA
Current Dissipation Variation (Load)	$\Delta I_{cc1d}$	$5mA \leq I_o \leq 1A$		0.5	mA
Output Noise Voltage	$V_{NO}$	$10Hz \leq f \leq 100kHz$ *		46	uV
Ripple Rejection	$R_r$	$f=120Hz$ , $10V \leq V_{IN} \leq 21V$	58	73	dB
Dropout Voltage	$V_{drop}$	$I_o=1A$	2.0		V
Output Short Current	$I_{os}$	$V_{IN}=35V$	0.75		A
Peak Output Current	$I_{op}$		2.2		A
Output Voltage at Strobe Mode	$V_{o(ston)}$	$V_{IN}=35V$ , $V_{st}=5V$ , $I_o=0$ , *		0.8	V
Current Dissipation at Strobe Mode	$I_{cc(ston)}$	"		3.0	mA
Strobe Input Current	$I_{st}$	"		1.0	mA

## L780S08

### Recommended Operating Conditions at Ta=25°C

Input Voltage Range	$V_{IN}$	10.5 to 23.0	V
Output Current Range	$I_o$	5 to 1000	mA

### Operating Characteristics at Tj=25°C, $V_{IN}=15V$ , $I_o=500mA$ , $V_{st}=0V$ , \*Ta=25°C

		min	typ	max	unit
Output Voltage 1	$V_{o1}$	7.7	8.0	8.3	V
Line Regulation 1	$\Delta V_{o1n1}$	$10.5V \leq V_{IN} \leq 25V$	6.0	160	mV
Line Regulation 2	$\Delta V_{o1n2}$	$11V \leq V_{IN} \leq 17V$	2.0	80	mV
Load Regulation 1	$\Delta V_{o1d1}$	$5mA \leq I_o \leq 1.5A$		160	mV
Load Regulation 2	$\Delta V_{o1d2}$	$250mA \leq I_o \leq 750mA$		80	mV
Output Voltage 2	$V_{o2}$	$10.5V \leq V_{IN} \leq 23V$ , $5mA \leq I_{IN} \leq 1A$	7.6	8.4	V
Current Dissipation	$I_{cc}$			8.0	mA
Current Dissipation Variation (Line)	$\Delta I_{cc1n}$	$10.5V \leq V_{IN} \leq 25V$		1.0	mA
Current Dissipation Variation (Load)	$\Delta I_{cc1d}$	$5mA \leq I_o \leq 1A$		0.5	mA
Output Noise Voltage	$V_{NO}$	$10Hz \leq f \leq 100kHz$ *		52	uV
Ripple Rejection	$R_r$	$f=120Hz$ , $11.5V \leq V_{IN} \leq 21.5V$	56	72	dB
Dropout Voltage	$V_{drop}$	$I_o=1A$	2.0		V
Output Short Current	$I_{os}$	$V_{IN}=35V$	0.75		A
Peak Output Current	$I_{op}$		2.2		A
Output Voltage at Strobe Mode	$V_{o(ston)}$	$V_{IN}=35V$ , $V_{st}=5V$ , $I_o=0$ , *		0.8	V
Current Dissipation at Strobe Mode	$I_{cc(ston)}$	"		3.0	mA
Strobe Input Current	$I_{st}$	"		1.0	mA

# L780S00 Series

## L780S09

### Recommended Operating Conditions at Ta=25°C

Input Voltage Range	$V_{IN}$	11.5 to 25.0	V
Output Current Range	$I_o$	5 to 1000	mA

### Operating Characteristics at Tj=25°C, $V_{IN}=16V$ , $I_o=500mA$ , $V_{st}=0V$ , \*Ta=25°C

		min	typ	max	unit
Output Voltage 1	$V_{o1}$	8.64	9.0	9.36	V
Line Regulation 1	$\Delta V_{o1n1}$	$11.5V \leq V_{IN} \leq 25V$	7	180	mV
Line Regulation 2	$\Delta V_{o1n2}$	$12V \leq V_{IN} \leq 20V$	2	90	mV
Load Regulation 1	$\Delta V_{o1d1}$	$5mA \leq I_o \leq 1.5A$		180	mV
Load Regulation 2	$\Delta V_{o1d2}$	$250mA \leq I_o \leq 750mA$		90	mV
Output Voltage 2	$V_{o2}$	$11.5V \leq V_{IN} \leq 24V$ , $5mA \leq I_o \leq 1A$	8.55	9.45	V
Current Dissipation	$I_{cc}$			8.0	mA
Current Dissipation Variation (Line)	$\Delta I_{cc1n}$	$11.5V \leq V_{IN} \leq 26V$		1.0	mA
Current Dissipation Variation (Load)	$\Delta I_{cc1d}$	$5mA \leq I_o \leq 1A$		0.5	mA
Output Noise Voltage	$V_{NO}$	$10Hz \leq f \leq 100kHz$ *	57		uV
Ripple Rejection	$R_r$	$f=120Hz$ , $12V \leq V_{IN} \leq 22V$	56	72	dB
Dropout Voltage	$V_{drop}$	$I_o=1A$	2.0		V
Output Short Current	$I_{os}$	$V_{IN}=35V$	0.75		A
Peak Output Current	$I_{op}$		2.2		A
Output Voltage at Strobe Mode	$V_{o(ston)}$	$V_{IN}=35V$ , $V_{st}=5V$ , $I_o=0$ , *		0.8	V
Current Dissipation at Strobe Mode	$I_{cc(ston)}$	"		3.0	mA
Strobe Input Current	$I_{st}$	"		1.0	mA

## L780S10

### Recommended Operating Conditions at Ta=25°C

Input Voltage Range	$V_{IN}$	13.0 to 25.0	V
Output Current Range	$I_o$	5 to 1000	mA

### Operating Characteristics at Tj=25°C, $V_{IN}=17V$ , $I_o=500mA$ , $V_{st}=0V$ , \*Ta=25°C

		min	typ	max	unit
Output Voltage 1	$V_{o1}$	9.6	10.0	10.4	V
Line Regulation 1	$\Delta V_{o1n1}$	$12.5V \leq V_{IN} \leq 28V$	8	200	mV
Line Regulation 2	$\Delta V_{o1n2}$	$14V \leq V_{IN} \leq 20V$	2.5	100	mV
Load Regulation 1	$\Delta V_{o1d1}$	$5mA \leq I_o \leq 1.5A$		200	mV
Load Regulation 2	$\Delta V_{o1d2}$	$250mA \leq I_o \leq 750mA$		100	mV
Output Voltage 2	$V_{o2}$	$12.5V \leq V_{IN} \leq 25V$ , $5mA \leq I_o \leq 1A$	9.5	10.5	V
Current Dissipation	$I_{cc}$			8.0	mA
Current Dissipation Variation (Line)	$\Delta I_{cc1n}$	$12.5V \leq V_{IN} \leq 25V$		1.0	mA
Current Dissipation Variation (Load)	$\Delta I_{cc1d}$	$5mA \leq I_o \leq 1A$		0.5	mA
Output Noise Voltage	$V_{NO}$	$10Hz \leq f \leq 100kHz$ *	63		uV
Ripple Rejection	$R_r$	$f=120Hz$ , $13V \leq V_{IN} \leq 23V$	55	72	dB
Dropout Voltage	$V_{drop}$	$I_o=1A$	2.0		V
Output Short Current	$I_{os}$	$V_{IN}=35V$	0.75		A
Peak Output Current	$I_{op}$		2.2		A
Output Voltage at Strobe Mode	$V_{o(ston)}$	$V_{IN}=35V$ , $V_{st}=5V$ , $I_o=0$ , *		0.8	V
Current Dissipation at Strobe Mode	$I_{cc(ston)}$	"		3.0	mA
Strobe Input Current	$I_{st}$	"		1.0	mA

# L780S00 Series

## L780S12

### Recommended Operating Conditions at $T_a=25^{\circ}\text{C}$

Input Voltage Range	$V_{IN}$	15.0 to 27.0	V
Output Current Range	$I_o$	5 to 1000	mA

### Operating Characteristics at $T_j=25^{\circ}\text{C}$ , $V_{IN}=19\text{V}$ , $I_o=500\text{mA}$ , $V_{st}=0\text{V}$ , $*T_a=25^{\circ}\text{C}$

			min	typ	max	unit
Output Voltage 1	$V_{o1}$		11.5	12.0	12.5	V
Line Regulation 1	$\Delta V_{oln1}$	$14.5\text{V} \leq V_{IN} \leq 30\text{V}$		10	240	mV
Line Regulation 2	$\Delta V_{oln2}$	$16\text{V} \leq V_{IN} \leq 22\text{V}$		3	120	mV
Load Regulation 1	$\Delta V_{old1}$	$5\text{mA} \leq I_o \leq 1.5\text{A}$			240	mV
Load Regulation 2	$\Delta V_{old2}$	$250\text{mA} \leq I_o \leq 750\text{mA}$			120	mV
Output Voltage 2	$V_{o2}$	$14.5\text{V} \leq V_{IN} \leq 27\text{V}$ , $5\text{mA} \leq V_{IN} \leq 1\text{A}$	11.4		12.6	V
Current Dissipation	$I_{cc}$				8.0	mA
Current Dissipation Variation (Line)	$\Delta I_{ccln}$	$14.5\text{V} \leq V_{IN} \leq 30\text{V}$			1.0	mA
Current Dissipation Variation (Load)	$\Delta I_{ccld}$	$5\text{mA} \leq I_o \leq 1\text{A}$			0.5	mA
Output Noise Voltage	$V_{NO}$	$10\text{Hz} \leq f \leq 100\text{kHz}$ *		75		$\mu\text{V}$
Ripple Rejection	$R_r$	$f=120\text{Hz}$ , $15\text{V} \leq V_{IN} \leq 25\text{V}$	55	71		dB
Dropout Voltage	$V_{drop}$	$I_o=1\text{A}$		2.0		V
Output Short Current	$I_{os}$	$V_{IN}=35\text{V}$		0.75		A
Peak Output Current	$I_{op}$			2.2		A
Output Voltage at Strobe Mode	$V_{o(ston)}$	$V_{IN}=35\text{V}$ , $V_{st}=5\text{V}$ , $I_o=0$ , *			0.8	V
Current Dissipation at Strobe Mode	$I_{cc(ston)}$	"			3.0	mA
Strobe Input Current	$I_{st}$	"			1.0	mA

## L780S15

### Recommended Operating Conditions at $T_a=25^{\circ}\text{C}$

Input Voltage Range	$V_{IN}$	18.0 to 30.0	V
Output Current Range	$I_o$	5 to 1000	mA

### Operating Characteristics at $T_j=25^{\circ}\text{C}$ , $V_{IN}=23\text{V}$ , $I_o=500\text{mA}$ , $V_{st}=0\text{V}$ , $*T_a=25^{\circ}\text{C}$

			min	typ	max	unit
Output Voltage 1	$V_{o1}$		14.4	15.0	15.6	V
Line Regulation 1	$\Delta V_{oln1}$	$17.5\text{V} \leq V_{IN} \leq 30\text{V}$		11	300	mV
Line Regulation 2	$\Delta V_{oln2}$	$20\text{V} \leq V_{IN} \leq 26\text{V}$		3	150	mV
Load Regulation 1	$\Delta V_{old1}$	$5\text{mA} \leq I_o \leq 1.5\text{A}$			300	mV
Load Regulation 2	$\Delta V_{old2}$	$250\text{mA} \leq I_o \leq 750\text{mA}$			150	mV
Output Voltage 2	$V_{o2}$	$17.5\text{V} \leq V_{IN} \leq 30\text{V}$ , $5\text{mA} \leq V_{IN} \leq 1\text{A}$	14.25		15.75	V
Current Dissipation	$I_{cc}$				8.0	mA
Current Dissipation Variation (Line)	$\Delta I_{ccln}$	$17.5\text{V} \leq V_{IN} \leq 30\text{V}$			1.0	mA
Current Dissipation Variation (Load)	$\Delta I_{ccld}$	$5\text{mA} \leq I_o \leq 1\text{A}$			0.5	mA
Output Noise Voltage	$V_{NO}$	$10\text{Hz} \leq f \leq 100\text{kHz}$ *		90		$\mu\text{V}$
Ripple Rejection	$R_r$	$f=120\text{Hz}$ , $18.5\text{V} \leq V_{IN} \leq 28.5\text{V}$	54	70		dB
Dropout Voltage	$V_{drop}$	$I_o=1\text{A}$		2.0		V
Output Short Current	$I_{os}$	$V_{IN}=35\text{V}$		0.75		A
Peak Output Current	$I_{op}$			2.2		A
Output Voltage at Strobe Mode	$V_{o(ston)}$	$V_{IN}=35\text{V}$ , $V_{st}=5\text{V}$ , $I_o=0$ , *			0.8	V
Current Dissipation at Strobe Mode	$I_{cc(ston)}$	"			3.0	mA
Strobe Input Current	$I_{st}$	"			1.0	mA

# L780S00 Series

## L780S18

### Recommended Operating Conditions at Ta=25°C

Input Voltage Range	$V_{IN}$	21.0 to 33.0	V
Output Current Range	$I_O$	5 to 1000	mA

### Operating Characteristics at Tj=25°C, $V_{IN}=27V$ , $I_O=500mA$ , $V_{st}=0V$ , \*Ta=25°C

			min	typ	max	unit
Output Voltage 1	$V_{O1}$		17.3	18.0	18.7	V
Line Regulation 1	$\Delta V_{Oln1}$	$21V \leq V_{IN} \leq 33V$		15	360	mV
Line Regulation 2	$\Delta V_{Oln2}$	$24V \leq V_{IN} \leq 30V$		5	180	mV
Load Regulation 1	$\Delta V_{old1}$	$5mA \leq I_O \leq 1.5A$			360	mV
Load Regulation 2	$\Delta V_{old2}$	$250mA \leq I_O \leq 750mA$			180	mV
Output Voltage 2	$V_{O2}$	$21V \leq V_{IN} \leq 33V$ , $5mA \leq V_{IN} \leq 1A$	17.1		18.9	V
Current Dissipation	$I_{cc}$				8.0	mA
Current Dissipation Variation (Line)	$\Delta I_{ccln}$	$21V \leq V_{IN} \leq 33V$			1.0	mA
Current Dissipation Variation (Load)	$\Delta I_{ccld}$	$5mA \leq I_O \leq 1A$			0.5	mA
Output Noise Voltage	$V_{NO}$	$10Hz \leq f \leq 100kHz$ *		110		uV
Ripple Rejection	$R_r$	$f=120Hz$ , $22V \leq V_{IN} \leq 32V$	53	69		dB
Dropout Voltage	$V_{drop}$	$I_O=1A$		2.0		V
Output Short Current	$I_{os}$	$V_{IN}=35V$		0.75		A
Peak Output Current	$I_{op}$			2.2		A
Output Voltage at Strobe Mode	$V_{O(ston)}$	$V_{IN}=35V$ , $V_{st}=5V$ , $I_O=0$ , *			0.8	V
Current Dissipation at Strobe Mode	$I_{cc(ston)}$	"			3.0	mA
Strobe Input Current	$I_{st}$	"			1.0	mA

## L780S20

### Recommended Operating Conditions at Ta=25°C

Input Voltage Range	$V_{IN}$	23.0 to 35.0	V
Output Current Range	$I_O$	5 to 1000	mA

### Operating Characteristics at Tj=25°C, $V_{IN}=29V$ , $I_O=500mA$ , $V_{st}=0V$ , \*Ta=25°C

			min	typ	max	unit
Output Voltage 1	$V_{O1}$		19.2	20.0	20.8	V
Line Regulation 1	$\Delta V_{Oln1}$	$23V \leq V_{IN} \leq 35V$		15	400	mV
Line Regulation 2	$\Delta V_{Oln2}$	$26V \leq V_{IN} \leq 32V$		5	200	mV
Load Regulation 1	$\Delta V_{old1}$	$5mA \leq I_O \leq 1.5A$			400	mV
Load Regulation 2	$\Delta V_{old2}$	$250mA \leq I_O \leq 750mA$			200	mV
Output Voltage 2	$V_{O2}$	$24V \leq V_{IN} \leq 35V$ , $5mA \leq V_{IN} \leq 1A$	19.0		21.0	V
Current Dissipation	$I_{cc}$				8.0	mA
Current Dissipation Variation (Line)	$\Delta I_{ccln}$	$23V \leq V_{IN} \leq 35V$			1.0	mA
Current Dissipation Variation (Load)	$\Delta I_{ccld}$	$5mA \leq I_O \leq 1A$			0.5	mA
Output Noise Voltage	$V_{NO}$	$10Hz \leq f \leq 100kHz$ *		110		uV
Ripple Rejection	$R_r$	$f=120Hz$ , $24V \leq V_{IN} \leq 34V$	53	67		dB
Dropout Voltage	$V_{drop}$	$I_O=1A$		2.0		V
Output Short Current	$I_{os}$	$V_{IN}=35V$		0.75		A
Peak Output Current	$I_{op}$			2.2		A
Output Voltage at Strobe Mode	$V_{O(ston)}$	$V_{IN}=35V$ , $V_{st}=5V$ , $I_O=0$ , *			0.8	V
Current Dissipation at Strobe Mode	$I_{cc(ston)}$	"			3.0	mA
Strobe Input Current	$I_{st}$	"			1.0	mA

# L780S00 Series

## L780S24


### Recommended Operating Conditions at $T_a=25^{\circ}\text{C}$

Input Voltage Range	$V_{IN}$	27.0 to 35.0	V
Output Current Range	$I_o$	5 to 1000	mA









### Operating Characteristics at $T_j=25^{\circ}\text{C}, V_{IN}=33\text{V}, I_o=500\text{mA}, V_{st}=0\text{V}, *T_a=25^{\circ}\text{C}$

			min	typ	max	unit
Output Voltage 1	$V_{o1}$		23.0	24.0	25.0	V
Line Regulation 1	$\Delta V_{o1n1}$	$27\text{V} \leq V_{IN} \leq 35\text{V}$		18	480	mV
Line Regulation 2	$\Delta V_{o1n2}$	$30\text{V} \leq V_{IN} \leq 35\text{V}$		6	240	mV
Load Regulation 1	$\Delta V_{o1d1}$	$5\text{mA} \leq I_o \leq 1.5\text{A}$			480	mV
Load Regulation 2	$\Delta V_{o1d2}$	$250\text{mA} \leq I_o \leq 750\text{mA}$			240	mV
Output Voltage 2	$V_{o2}$	$27\text{V} \leq V_{IN} \leq 35\text{V},$ $5\text{mA} \leq V_{IN} \leq 1\text{A}$	22.8		25.2	V
Current Dissipation	$I_{cc}$				8.0	mA
Current Dissipation Variation (Line)	$\Delta I_{cc1n}$	$27\text{V} \leq V_{IN} \leq 35\text{V}$			1.0	mA
Current Dissipation Variation (Load)	$\Delta I_{cc1d}$	$5\text{mA} \leq I_o \leq 1\text{A}$			0.5	mA
Output Noise Voltage	$V_{NO}$	$10\text{Hz} \leq f \leq 100\text{kHz}^*$		180		$\mu\text{V}$
Ripple Rejection	$R_r$	$f=120\text{Hz},$ $28\text{V} \leq V_{IN} \leq 34\text{V}$	50	66		dB
Dropout Voltage	$V_{drop}$	$I_o=1\text{A}$		2.0		V
Output Short Current	$I_{os}$	$V_{IN}=35\text{V}$		0.75		A
Peak Output Current	$I_{op}$			2.2		A
Output Voltage at Strobe Mode	$V_{o(ston)}$	$V_{IN}=35\text{V}, V_{st}=5\text{V},$ $I_o=0, *$			0.8	V
Current Dissipation at Strobe Mode	$I_{cc(ston)}$	"			3.0	mA
Strobe Input Current	$I_{st}$	"			1.0	mA




### Equivalent Circuit Block Diagram



# L780S00 Series







■ No products described or contained herein are intended for use in surgical implants, life-support systems, aerospace equipment, nuclear power control systems, vehicles, disaster/crime-prevention equipment and the like, the failure of which may directly or indirectly cause injury, death or property loss.

■ Anyone purchasing any products described or contained herein for an above-mentioned use shall:

- ① Accept full responsibility and indemnify and defend SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors and all their officers and employees, jointly and severally, against any and all claims and litigation and all damages, cost and expenses associated with such use;
- ② Not impose any responsibility for any fault or negligence which may be cited in any such claim or litigation on SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors or any of their officers and employees jointly or severally.

■ Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.